

**EFA+™**

WOOD FLOORING ADHESIVE AND MOISTURE VAPOR RETARDER


**IN STOCK**  
**5 GALLON**
**\$212<sup>99</sup>**

sku:BOSTEFA5

## KEY FEATURES

- Easy spread
- Great ridge retention
- Low VOC

## Flooring Types

- Solid hardwood
- Engineered hardwood
- Bamboo
- Cork
- Parquet
- Plywood
- Ceramic tile, marble, stone inlays (residential or light commercial only)

## Substrates

- Concrete
- Plywood / OSB
- Well-bonded vinyl
- Terrazzo
- Radiant-heat flooring
- Cement backer board
- Gypsum underlayments (dry, above-grade)
- Cement patch/underlayments

## DESCRIPTION

EFA+™ Elastomeric Flooring Adhesive is an easy-to-trowel urethane adhesive and moisture control membrane. It provides a tough, flexible, tenacious bond to a variety of surfaces. Bostik's EFA+™ elastomeric characteristics allow the adhesive to move with the wood as it expands and contracts over the life of the floor. Bostik's EFA+™ exhibits a long open time making installation easier and faster.

**Ultimate**

ADHESIVE REMOVER


**IN STOCK**  
**TOWEL WIPES**
**\$34<sup>99</sup>**

sku:BOSTTOWEL

## KEY FEATURES

- Ready to use
- Removes cured adhesive
- Residue Free

## Application

- Open lid and pull out towels.
- Rub area of the floor that has cured or wet adhesive using a presoaked towel.
- If adhesive has cured for more than two days, lay a towel over cured adhesive and let it stand for approximately 5 minutes.
- Wipe area clean with a fresh towel.

**NOTE:** Do not allow excess remover to drip between floor boards.

## DESCRIPTION

Bostik's Ultimate™ Adhesive Remover is a readily biodegradable, low odor, water rinseable solution. Use Ultimate™ to remove wet and cured urethane adhesive from the surface of pre-finished (non-wax) wood flooring.

Please carefully read the install guidelines for proper job related installation method.