

EFA+™

WOOD FLOORING ADHESIVE AND MOISTURE VAPOR RETARDER



in stock
5 GALLON
\$139
BOSTEFA5

DESCRIPTION

EFA+™ Elastomeric Flooring Adhesive is an easy-to-trowel urethane adhesive and moisture control membrane. It provides a tough, flexible, tenacious bond to a variety of surfaces. Bostik's EFA+™ elastomeric characteristics allow the adhesive to move with the wood as it expands and contracts over the life of the floor. Bostik's EFA+™ exhibits a long open time making installation easier and faster. This adhesive has low VOC's and does NOT contain any water.

Use Environments

- Residential
- Offices/light commercial
- Heavy commercial

Substrates

- Concrete
- Plywood
- OSB
- Well-bonded vinyl
- Terrazzo
- Ceramic tile
- Cement backer board
- Gypsum underlayments (dry, above-grade)
- Cement patch/underlayments

Flooring Types

- Solid hardwood
- Engineered hardwood
- Bamboo
- Cork
- Parquet
- Plywood
- Ceramic tile, marble, stone inlays (residential or light commercial only)

GREENFORCE™

ADVANCED TRI-LINKING™ ADHESIVE AND MOISTURE CONTROL MEMBRANE



in stock
4 GALLON
\$174
BOSTGREENF4

DESCRIPTION

Bostik GreenForce™ is a high performance hardwood flooring adhesive and moisture control membrane that maintains the superior long term durability and moisture protection properties of high-end urethane adhesives but is easier to spread and clean even after full cure.

Use Environments

- Residential
- Offices/light commercial
- Heavy commercial

Substrates

- Concrete
- Plywood
- OSB
- Well-bonded vinyl
- Terrazzo
- Ceramic tile
- Cement backer board
- Gypsum underlayments (dry, above-grade)
- Cement patch/underlayments

Flooring Types

- Solid hardwood
- Engineered hardwood
- Bamboo
- Cork
- Parquet
- Plywood
- Ceramic tile, marble, stone inlays (residential or light commercial only)

Ultimate™

ADHESIVE REMOVER



in stock
TOWEL WIPES
\$34.99
BOSTTOWEL

DESCRIPTION

Bostik's Ultimate™ Adhesive Remover is a readily biodegradable, low odor, water rinseable solution. Use Ultimate™ to remove wet and cured urethane adhesive from the surface of pre-finished (non-wax) wood flooring.

Key Features

- Ready to use
- Removes cured adhesive
- Residue Free

Application

- Open lid and pull out towels.
- Rub area of the floor that has cured or wet adhesive using a presoaked towel.
- If adhesive has cured for more than two days, lay a towel over cured adhesive and let it stand for approximately 5 minutes.
- Wipe area clean with a fresh towel.

NOTE: Do not allow excess remover to drip between floor boards.

Please carefully read the install guidelines for proper job related installation method.

*pricing subject to change without notice, product availability may vary.

5/26/2020