



# Tub & Tile Caulk™

SILCONIZED ACRYLIC CAULK

## KEY FEATURES

- Compliments Bostik grout colors
- Mold & mildew resistant after cure
- Flexible & water cleanable

## DESCRIPTION

Tub & Tile Caulk™ is a siliconized acrylic caulk provides a flexible seal that bonds to most common household surfaces. Ideal for filling joints where tiles abut dissimilar surfaces. Tub and Tile Caulk™ match the color and texture of Bostik grout colors. Use around bathtub, showers, countertops, basins and many other areas. Meets or exceed ASTM C834 standard specification for latex sealants.

## WHERE TO USE

Interior, floor and wall.

## DIRECTIONS FOR USE

Read and understand technical and safety data sheet completely prior to installation. Always do a test to ensure product satisfaction and/or to become familiar with proper application techniques prior to use.

**Grout joint sizes:** For filling joints where tiles abuts dissimilar surfaces. For caulking around sinks, tubs, showers, countertops, ceramic tile and natural stone. Ideal flexible joint between horizontal and vertical surfaces.

## SURFACE PREPARATION

All surfaces must be clean, dry and free from dirt, dust, grease, oil, mildew, wax, loose paint & old caulking. Remove mildew by scrubbing with a solution of 4oz. TSP (Trisodium Phosphate), 1 quart of liquid bleach mixed with 3 quarts of warm water. Protect eyes and hands by wearing goggles and water and chemical-resistant gloves. Thoroughly rinse surface and allow to dry completely before caulking.

**Note:** It is the user's responsibility to determine the condition and suitability of all surfaces before application.

## APPLICATION

Apply only when caulk, air and substrate temperatures are above 50°F (10°C) 90°F (32°C). Cut cartridge nozzle at a 45° angle to desired size and puncture inner foil seal. For a neat, straight edge, mask



both sides of joint with painters tape. Insert cartridge into caulking gun. Apply caulking while holding at a 45° angle using steady even pressure. After installation the joint should be immediately smoothed with a spatula, spoon or wet finger to reduce voids and create a smooth appearance. Wipe away excess with damp cloth before surface skins over. Protect from water until cured (24 hours) May be painted over in 4-6 hours depending on climatic conditions. Larger beads may require longer drying time due to temperature and humidity.

## TECHNICAL DATA

- Meets ASTM C834 for low-movement sealant
- Freeze / Thaw Stable
- UV-Stable
- Mold & Mildew Resistant

## CLEAN UP

Clean all tools with soap and warm water. Remove cured caulk with a sharp blade. Clean your skin and equipment immediately after use with warm water and a mild soap.

APPROXIMATE COVERAGE CHART								
Coverage for 10.1 fl. oz. (298 ml) Cartridge								
Depth	Width							
	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/8"	99	49	33	24	20	16	14	12
1/4"		24	20	12	10	8	7	6
3/8"			11	8	6	5	5	4
1/2"				6	5	4	3	3

Linear Feet per 10.1 fl. oz. Cartridge

### FOR BEST RESULTS

- Apply caulk in temperatures between 50°F (10°C) & 90°F (32°C).
- Store caulk at temperatures between 40°F (10°C) & 90°F (32°C).
- Do not use for automobile, marine or below waterline applications.
- Do not use for filling butt joints, correcting surface defects or for tuck pointing.
- Allow new concrete to cure for 30 days before caulking.
- Do not use for joints subject to heavy abrasion or wear.
- Do not attempt to thin caulk with solvents or water.
- Prime bare surfaces before caulking.
- For a neat, straight bead edge, mask both sides of joint with masking tape.
- Do not "overtool" the applied caulk, leaving too little caulk to perform properly.
- Allow a minimum of 4 to 6 hours drying time before painting.

### PACKAGING

10.1 oz cartridges (6/case).

Sold in full cases only. Available in most Bostik grout colors in sanded and unsanded formulas. Check with customer service or your Bostik Territory Manager.

### PRECAUTIONS

Use with adequate ventilation. Avoid prolonged exposure to vapors. Avoid contact with skin and eyes.

### STORAGE/SHELF LIFE

Store in a clean, dry area, not affected by freezing or hot temperatures between 40°F (4°C) and 90°F (32°C). Two years from the date of manufacturing.

### VOC

< 25 g/L (< 1.5 %)

### LIMITATIONS

- Apply only to clean, dry, frost-free surfaces.
- Intermit exposure to water for 72 hours.
- Not recommended for use underwater or below grade.
- Cold temperatures & high humidity will slow down cure time.
- Not for use in joints subjected to high degrees of movement. (Use Bostik 915FS™ or 955-SL™).
- NOT FOR USE IN STEAM ROOMS OR COMMERCIAL KITCHENS & SHOWERS.
- For interior, residential or light commercial use only.

\*\* Joint size should not exceed 1/2 inch x 1/2 inch; if joint exceeds 3/8 inch width x 1/4 inch depth, use appropriate closed-cell backer rod.

### CAUTION

CONTENTS MAY BE HARMFUL IF SWALLOWED, INHALED OR BY SKIN CONTACT. CONTAINS POTENTIAL SENSITIZER. MAY CAUSE ALLERGIC SKIN OR LUNG REACTION. IRRITANT. MAY IRRITATE EYES, SKIN OR RESPIRATORY TRACT. Though encapsulated, this product contains known and suspected carcinogens. Do not breathe fumes. Do not get in eyes, on skin or on clothing. Do not swallow. Handle with care. Use only in a well-ventilated area or wear a mask. Wear protective clothing including gloves. Wash thoroughly after handling. Store in a cool, dry area. Do not reuse container.

### KEEP OUT OF REACH OF CHILDREN

### FIRST AID TREATMENT

Contains calcium carbonate, quartz silica, titanium dioxide and carbon black inextricably bound in a polymer matrix. If in eyes or on skin, rinse well with water. If on clothes, remove clothes. If inhaled, move person into fresh air. If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting.

### SEE SAFETY DATA SHEET

**CHEMICAL EMERGENCY:** 800-424-9300 (USA), 703-527-3887 (International)

**MEDICAL EMERGENCY:** 866-767-5089

### LIMITED WARRANTY

It is the buyer's obligation to test the suitability of the product for an intended use prior to using it. The Limited Warranty extends only to the original purchaser and is not transferable or assignable. Any claim for a defective product must be filed within 30 days of discovery of a problem, and must be submitted with written proof of purchase. Limited Warranty found at [www.bostik.com/us](http://www.bostik.com/us) or call 800.726.7845. TO THE MAXIMUM EXTENT ALLOWED BY LAW, BOSTIK DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. UNLESS OTHERWISE STATED IN THE LIMITED WARRANTY, THE SOLE REMEDY FOR BREACH OF WARRANTY IS REPLACEMENT OF THE PRODUCT OR CREDIT OF THE BUYER'S PURCHASE PRICE. BOSTIK DISCLAIMS ANY LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES TO THE MAXIMUM EXTENT ALLOWED BY LAW. DISCLAIMERS OF IMPLIED WARRANTIES MAY NOT BE APPLICABLE TO CERTAIN CLASSES OF BUYERS AND SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS MAY NOT APPLY TO YOU.

### BOSTIK HOTLINE

**Smart help**  
**1-800-726-7845**

### Bostik, Inc.

11320 W. Watertown Plank Road  
Wauwatosa, WI 53226

[www.bostik.com/us](http://www.bostik.com/us)

